

Design & Size Options



LIVINGSTON		PASSAGE													BIFOLDS											
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	16"	18"	24"	28"	30"	32"	36"	48"	60"	72"	
	LIVINGSTON.. (3 PANEL)																									
	Livingston 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Livingston 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Livingston 96"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

HERITAGE SERIES		PASSAGE													BIFOLDS											
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	16"	18"	24"	28"	30"	32"	36"	48"	60"	72"	
	LINCOLN PARK.. (1 PANEL)																									
	Craftsman 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 96"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	LOGAN.. (2 PANELS)																									
	Craftsman 80"	•*▲	•▲	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•▲	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 96"	•*▲	•▲	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	WINSLOW.. (3 PANELS)																									
	Craftsman 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

WEST END COLLECTION		PASSAGE													BIFOLDS											
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	16"	18"	24"	28"	30"	32"	36"	48"	60"	72"	
	MELROSE																									
	Embossed Groove 80"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Embossed Groove 84"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	BERKLEY																									
	Embossed Groove 80"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Embossed Groove 84"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

MOLDED PANEL SERIES		PASSAGE													BIFOLDS											
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	16"	18"	24"	28"	30"	32"	36"	48"	60"	72"	
	CHEYENNE																									
	Cheyenne 80"	•*▲	•*▲	•▲	•	•*▲	•	•*▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Cheyenne 96"	•*▲	•*▲	•▲	•	•*▲	•	•*▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	RIVERSIDE																									
	Riverside 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Riverside 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Riverside 96"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options



MOLDED PANEL SERIES		PASSAGE														BIFOLDS										
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	16"	18"	24"	28"	30"	32"	36"	48"	60"	72"
	2 PANEL ARCH-TOP																									
		Smooth C&B 80"	•*	•*	•*	•*	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth C&B 84"	•*	•*	•*	•*	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 96"	•*	•*	•▲	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Textured C&B 80"	•*	•▲	•▲	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	2 PANEL ROMAN																									
		Smooth INP 80"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 84"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Smooth INP 96"				•*	•▲	•*	•	•	•	•	•	•	•	•					•	•	•		•	•	
	2 PANEL																									
		Smooth INP 80"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 84"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Smooth INP 96"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	4 PANEL																									
		Smooth INP 80"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 84"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Smooth INP 96"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	6 PANEL																									
		Smooth INP 80"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 84"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Smooth INP 96"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Textured C&B 80"	•*	•▲	•▲	•	•*	•▲	•*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
		Textured C&B 84"								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Textured C&B 96"								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	2 PANEL COMMERCIAL																									
		Smooth INP 80"																								
	Smooth INP 84"																									
	6 PANEL COMMERCIAL																									
		Smooth INP 80"																								
	Smooth INP 84"																									

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs




LIVINGSTON.		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
		LIVINGSTON. (3 PANEL)											
		12" 14" 15" 16"	80" 84" 96"	3	1-3/8" 1-3/4"	6.5"	2.75 (12") [▲] 3.75 (14") 4.25 (15") 4.75 (16")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		18" 20"	80" 84" 96"	3	1-3/8" 1-3/4"	8.50"	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		22" 24" 26"	80" 84" 96"	3	1-3/8" 1-3/4"	14.5"	3.75 (22") [▲] 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		28"	80" 84" 96"	3	1-3/8" 1-3/4"	18.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		30"	80" 84" 96"	3	1-3/8" 1-3/4"	20.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		32" 34"	80" 84" 96"	3	1-3/8" 1-3/4"	22.50"	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
		36"	80" 84" 96"	3	1-3/8" 1-3/4"	26.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth


LIVINGSTON. BIFOLD		WIDTH NOMINAL	HEIGHT NOMINAL	WIDTH ACTUAL	HEIGHT ACTUAL	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER STILES	TOP RAIL	LOCK RAIL	BOTTOM RAIL
		LIVINGSTON. (3 PANEL)											
		18"	80" 84" 96"	17.5"	79" 83" 95"	6	1-3/8"	5.375	1.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		24"	80" 84" 96"	23.5"	79" 83" 95"	6	1-3/8"	5.375	4.625	1.75	4.25 (80") 6.25 (84") 4.25 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		28"	80" 84" 96"	27.5"	79" 83" 95"	6	1-3/8"	8.375	3.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		30"	80" 84" 96"	29.5"	79" 83" 95"	6	1-3/8"	8.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		32"	80" 84" 96"	31.5"	79" 83" 95"	6	1-3/8"	11.375	2.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		36"	80" 84" 96"	35.5"	79" 83" 95"	6	1-3/8"	11.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		48"	80" 84" 96"	47.5"	79" 83" 95"	12	1-3/8"	5.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		60"	80" 84" 96"	59.5"	79" 83" 95"	12	1-3/8"	8.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
		72"	80" 84" 96"	71.5"	79" 83" 95"	12	1-3/8"	11.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs



HERITAGE SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
LINCOLN PARK.. (1 PANEL)													
	12"	80"	1	1-3/8"	5.75	3.12 (12") [▲] 4.12 (14") 4.62 (15") 5.12 (16")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	14"												
	15"												
	16"												
	18"	84"	1	1-3/8"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	20"												
	22"	80"	1	1-3/8"	14.5	3.75 (22") [▲] 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	24"												
	26"												
	28"	84"	1	1-3/8"	18.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	30"	80"	1	1-3/8"	20.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	32"	84"	1	1-3/8"	22.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	34"												
	36"	80"	1	1-3/8"	24.5	5.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	


HERITAGE SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
LOGAN.. (2 PANELS)													
	12"	80"	2	1-3/8"	6.5	2.75 (12") [▲] 3.75 (14") [▲] 4.25 (15") 4.75 (16")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	14"												
	15"												
	16"												
	18"	84"	2	1-3/8"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	20"												
	22"	80"	2	1-3/8"	14.5	3.75 (22") [▲] 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	24"												
	26"												
	28"	80"	2	1-3/8"	18.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	30"	84"	2	1-3/8"	20.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	32"	80"	2	1-3/8"	22.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	34"												
	36"	84"	2	1-3/8"	24.5	5.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	


HERITAGE SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
WINSLOW.. (3 PANELS)													
	12"	80"	2	1-3/8"	5.75	3.125 (12") [*] 4.125 (14") 4.625 (15") 5.125 (16")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	
	14"												
	15"												
	16"												
	18"	84"	2	1-3/8"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	
	20"												
	22"	80"	3	1-3/8"	14.5	3.75 (22") [▲] 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	24"												
	26"												
	28"	84"	3	1-3/8"	16.5	4.75 (28")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	
	30"	80"	3	1-3/8"	20.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	
	32"	84"	3	1-3/8"	24.5	4.75 (34") 5.75 (36")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	
	34"												
	36"	80"	3	1-3/8"	24.5	5.75 (36")	N/A	4.25 (80") 6.25 (84")	N/A	10.87 (80") 12.87 (84")	C	Smooth	

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs




WEST END COLLECTION. MELROSE.	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
	12" - 36"	80" 84"	6	1-3/8" 1-3/4"	12" - 36"	N/A	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth


WEST END COLLECTION. BERKLEY.	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
	12"	80" 84"	6	1-3/8" 1-3/4"	7.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	14"	80" 84"	6	1-3/8" 1-3/4"	9.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	15"	80" 84"	6	1-3/8" 1-3/4"	10.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	16"	80" 84"	6	1-3/8" 1-3/4"	11.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	18"	80" 84"	6	1-3/8" 1-3/4"	11.67	6.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	20"	80" 84"	6	1-3/8" 1-3/4"	13.67	6.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	22"	80" 84"	6	1-3/8" 1-3/4"	13.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	24"	80" 84"	6	1-3/8" 1-3/4"	15.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	26"	80" 84"	6	1-3/8" 1-3/4"	17.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	28"	80" 84"	6	1-3/8" 1-3/4"	18.67	9.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	30"	80" 84"	6	1-3/8" 1-3/4"	21.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	32"	80" 84"	6	1-3/8" 1-3/4"	23.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	34"	80" 84"	6	1-3/8" 1-3/4"	25.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	36"	80" 84"	6	1-3/8" 1-3/4"	27.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs



MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
CHEYENNE													
	12"	80"	2	1-3/8"	7.5	2.25 (12")**	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth	
	14"					3.25 (14")**							
	15"					3.75 (15")*							
	16"	4.25 (16")											
	18"	80"	2	1-3/8"	11.67	3.16 (18")**	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth	
	20"					4.16 (20")							
	22"	80"	2	1-3/8"	15.75	3.12 (22")**	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth	
	24"					4.12 (24")							
26"	5.12 (26")												
28"	80"	2	1-3/8"	19.75	4.12	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth		
30"	80"	2	1-3/8"	21.75	4.12	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth		
32"	80"	2	1-3/8"	23.75	4.12 (32")	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth		
34"	96"	2	1-3/4"	27.75	5.12 (34")	N/A	4.25 (96")	7	8.37 (96")	Chey	Smooth		
36"	80"	2	1-3/8"	27.75	4.12	N/A	4.25 (80")	7	8.37 (80")	Chey	Smooth		


MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
RIVERSIDE													
	12"	80"	5 (80", 84")	1-3/8"	5.75	3.12 (12")**	N/A	4.25 (80")	N/A	8.38 (80")	Riv	Smooth	
	14"					4.12 (14")							
	15"					4.62 (15")							
	16"	5.12 (16")											
	18"	80"	5 (80", 84")	1-3/8"	8.5	4.75 (18")	N/A	4.25 (80")	N/A	8.38 (80")	Riv	Smooth	
	20"	84"	6 (96")	1-3/4"	14.5	5.75 (20")	N/A	6.25 (84")	N/A	10.38 (84")	Riv	Smooth	
	22"	80"	5 (80", 84")	1-3/8"	18.5	3.75 (22")*	N/A	4.25 (80")	N/A	8.38 (80")	Riv	Smooth	
	24"	84"	6 (96")	1-3/4"	20.5	4.75 (24")	N/A	6.25 (84")	N/A	10.38 (84")	Riv	Smooth	
26"	96"	6 (96")	1-3/4"	22.5	5.75 (26")	N/A	4.25 (96")	N/A	8.38 (96")	Riv	Smooth		
28"	80"	5 (80", 84")	1-3/8"	26.5	4.75	N/A	4.25 (80")	N/A	8.38 (80")	Riv	Smooth		
30"	84"	6 (96")	1-3/4"	22.5	4.75 (32")	N/A	6.25 (84")	N/A	10.38 (84")	Riv	Smooth		
32"	84"	6 (96")	1-3/4"	22.5	5.75 (34")	N/A	4.25 (96")	N/A	8.38 (80")	Riv	Smooth		
34"	96"	6 (96")	1-3/4"	26.5	4.75	N/A	6.25 (84")	N/A	10.38 (84")	Riv	Smooth		
36"	80"	5 (80", 84")	1-3/8"	26.5	4.75	N/A	4.25 (80")	N/A	8.38 (80")	Riv	Smooth		
36"	84"	6 (96")	1-3/4"	26.5	4.75	N/A	6.25 (84")	N/A	10.38 (84")	Riv	Smooth		
36"	96"	6 (96")	1-3/4"	26.5	4.75	N/A	4.25 (96")	N/A	8.38 (96")	Riv	Smooth		


MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL ARCH-TOP (SMOOTH)													
	12"	80"	2	1-3/8"	9.5	1.25 (12")**	N/A	4.75 (80")	3.75	8.50 (80")	C&B (80", 84")	Smooth	
	14"					2.25 (14")**							
	15"					2.75 (15")*							
	16"					3.25 (16")**							
	12"	96"	2	1-3/8"	7.08	2.46 (12")**	N/A	6.75 (80")	3.70	8.50 (96")	INP (96")	Smooth	
	14"					3.46 (14")*							
	15"					3.96 (15")*							
	16"					4.46 (16")							
	18"	80"	2	1-3/8"	9.5	4.25 (18")	N/A	4.75 (80")	3.75 (80", 84")	8.50 (80")	C&B (80", 84")	Smooth	
	20"	84"	2	1-3/4"	14.96	5.25 (20")	N/A	6.75 (84")	3.70 (96")	10.50 (84")	INP (96")	Smooth	
	22"	80"	2	1-3/8"	18.1	3.52 (22")*	N/A	4.75 (80")	3.75 (80", 84")	8.50 (80")	C&B (80", 84")	Smooth	
	24"	84"	2	1-3/4"	19.69	4.52 (24")	N/A	6.75 (84")	3.70 (96")	10.50 (84")	C&B (80", 84")	Smooth	
26"	96"	2	1-3/4"	22.85	5.52 (26")	N/A	6.75 (96")	3.70 (96")	8.50 (96")	INP (96")	Smooth		
28"	80"	2	1-3/8"	22.85	4.95	N/A	4.75 (80")	3.75 (80", 84")	8.50 (80")	C&B (80", 84")	Smooth		
30"	84"	2	1-3/4"	22.85	5.15	N/A	6.75 (84")	3.70 (96")	10.50 (84")	C&B (80", 84")	Smooth		
32"	80"	2	1-3/8"	22.85	4.57 (32")	N/A	6.75 (84")	3.70 (96")	8.50 (80")	C&B (80", 84")	Smooth		
34"	96"	2	1-3/4"	25	5.57 (34")	N/A	6.75 (96")	3.70 (96")	10.50 (84")	INP (96")	Smooth		
36"	80"	2	1-3/8"	25	5.5	N/A	4.75 (80")	3.75 (80", 84")	8.50 (80")	C&B (80", 84")	Smooth		
36"	84"	2	1-3/4"	25	5.5	N/A	6.75 (84")	3.70 (96")	10.50 (84")	INP (96")	Smooth		
36"	96"	2	1-3/4"	25	5.5	N/A	6.75 (96")	3.70 (96")	8.50 (96")	INP (96")	Smooth		


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs



MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL ARCH-TOP (TEXTURED)													
	12"	80"	2	1-3/8" 1-3/4"	7	2.5 (12")**	N/A	4.75 (80")	3.74	8.51	C&B	Textured	
	14"					3.5 (14")*							
	15"					4.0 (15")*							
	16"					4.5 (16")							
	18"	80"	2	1-3/8" 1-3/4"	9.5	4.25 (18")	N/A	4.75 (80")	3.74	8.51	C&B	Textured	
	20"					5.25 (20")							
	22"					3.52 (22")**							
	24"					4.52 (24")							
26"	5.52 (26")												
28"	80"	2	1-3/8" 1-3/4"	18.1	4.95	N/A	4.75 (80")	3.74	8.51	C&B	Textured		
30"					5.15								
32"					4.57 (32")								
34"					5.57 (34")								
36"	80"	2	1-3/8" 1-3/4"	25	5.5	N/A	4.75 (80")	3.74	8.51	C&B	Textured		

MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL ROMAN													
	12"	80" 84"	2	1-3/8" 1-3/4"	7.08	2.45 (12")**	N/A	4.75 (80") 6.75 (84")	6.78	8.25 (80") 10.25 (84")	INP	Smooth	
	14"					3.45 (14")*							
	15"					3.95 (15")*							
	16"					4.45 (16")							
	18"	80" 84" 96"	2	1-3/8" 1-3/4"	11.96	3 (18")**	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	20"					4 (20")*							
	22"					3.15 (22")**							
	24"					4.15 (24")							
26"	5.15 (26")												
28"	80" 84" 96"	2	1-3/8" 1-3/4"	17.69	5.15	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
30"					5.15								
32"					5.15 (32")								
34"					6.15 (34")								
36"	80" 84" 96"	2	1-3/8" 1-3/4"	23.69	6.15	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		

MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL													
	12"	80" 84" 96"	2	1-3/8" 1-3/4"	7.08	2.45 (12")**	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	14"					3.45 (14")*							
	15"					3.95 (15")*							
	16"					4.45 (16")							
	18"	80" 84" 96"	2	1-3/8" 1-3/4"	11.96	3 (18")**	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	20"					4 (20")*							
	22"					3.15 (22")**							
	24"					4.15 (24")							
26"	5.15 (26")												
28"	80" 84" 96"	2	1-3/8" 1-3/4"	17.69	5.15	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
30"					5.15								
32"					5.15 (32")								
34"					6.15 (34")								
36"	80" 84" 96"	2	1-3/8" 1-3/4"	23.69	6.15	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs





MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
	4 PANEL												
	12"	80"	2	1-3/8" 1-3/4"	7.08	2.45 (12")** 3.45 (14")* 3.95 (15")* 4.45 (16")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	14"	84"											
	15"	84"											
	16"	96"											
	18"	80"	2	1-3/8" 1-3/4"	11.96	3 (18")** 4 (20")*	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	20"	84"											
	22"	80"	4	1-3/8" 1-3/4"	5.96	3.15 (22")** 4.15 (24") 5.15 (26")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
24"	84"												
26"	96"												
28"	80"	4	1-3/8" 1-3/4"	7.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
30"	80"	4	1-3/8" 1-3/4"	8.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
32"	80"	4	1-3/8" 1-3/4"	9.96	4.15 (32") 5.15 (34")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
34"	84"												
36"	80"	4	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
	6 PANEL (SMOOTH)												
	12"	80"	3	1-3/8" 1-3/4"	7.08	2.45 (12")** 3.45 (14")* 3.95 (15")* 4.45 (16")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	14"	84"											
	15"	84"											
	16"	96"											
	18"	80"	3	1-3/8" 1-3/4"	11.96	3 (18")** 4 (20")*	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
	20"	84"											
	22"	80"	6	1-3/8" 1-3/4"	5.96	3.15 (22")** 4.15 (24") 5.15 (26")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth	
24"	84"												
26"	96"												
28"	80"	6	1-3/8" 1-3/4"	7.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
30"	80"	6	1-3/8" 1-3/4"	8.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
32"	80"	6	1-3/8" 1-3/4"	9.96	4.15 (32") 5.15 (34")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
34"	84"												
36"	80"	6	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth		
84"	96"												
 <p>PRIMED & WHITE</p>	6 PANEL (TEXTURED)												
	12"	80"	3	1-3/8" 1-3/4"	7.08	2.45 (12")** 3.45 (14")* 3.95 (15")* 4.45 (16")	N/A	4.28	6.81	8.28	C&B	Textured	
	14"	84"											
	15"	84"											
	16"	96"											
	18"	80"	3	1-3/8" 1-3/4"	11.96	3 (18")** 4 (20")*	N/A	4.28	6.81	8.28	C&B	Textured	
	20"	84"											
	22"	80"	6	1-3/8" 1-3/4"	5.94	3.15 (22")** 4.15 (24") 5.15 (26")	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured	
24"	84"												
26"	96"												
28"	80"	6	1-3/8" 1-3/4"	7.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured		
84"	96"												
30"	80"	6	1-3/8" 1-3/4"	8.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured		
84"	96"												
32"	80"	6	1-3/8" 1-3/4"	9.94	4.15 (32") 5.15 (34")	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured		
34"	84"												
36"	80"	6	1-3/8" 1-3/4"	11.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured		
84"	96"												


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.
 ▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Dimensional Specs



MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
6 PANEL (TEXTURED)													
 <p>PRESTAINED</p>	12" 14" 15" 16"	80"	3	1-3/8" 1-3/4"	7.08	2.46 (12")** 3.46 (14")* 3.96 (15")* 4.46 (16")*	N/A	4.25	6.77	8.25	INP	Textured	
	18" 20" 22" 24" 26"	80"	3	1-3/8" 1-3/4"	11.96	3.02 (18")** 4.02 (20")* 3.15 (22")**	N/A	4.25	6.77	8.25	INP	Textured	
	28"	80"	6	1-3/8" 1-3/4"	5.96	4.15 (24") 5.15 (26")	3.78	4.25	6.77	8.25	INP	Textured	
	30"	80"	6	1-3/8" 1-3/4"	7.96	4.15	3.78	4.25	6.77	8.25	INP	Textured	
	32" 34"	80"	6	1-3/8" 1-3/4"	8.96	4.15 (32") 5.15 (34")	3.78	4.25	6.77	8.25	INP	Textured	
	36"	80"	6	1-3/8" 1-3/4"	9.96	4.15	3.78	4.25	6.77	8.25	INP	Textured	
	36"	80"	6	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25	6.77	8.25	INP	Textured	

MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL COMMERCIAL													
	30" 32"	80" 84"	2	1-3/8" 1-3/4"	19.69	5.15 (30") 6.15 (32")	N/A	4.75 (80") 6.75 (84")	6.78	10.87 (80") 12.87 (84")	INP	Smooth	
	34" 36"	80" 84"	2	1-3/8" 1-3/4"	23	5.5 (34") 6.5 (36")	N/A	4.75 (80") 6.7 (84")	6.78	10.87 (80") 12.87 (84")	INP	Smooth	

MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
6 PANEL COMMERCIAL													
	30" 32"	80" 84"	6	1-3/8" 1-3/4"	7.61	5.5 (30") 6.5 (32")	3.78	5.88 (80") 7.63 (84")	6.77	10.63 (80") 12.88 (84")	INP	Smooth	
	34" 36"	80" 84"	6	1-3/8" 1-3/4"	9.61	5.5 (34") 6.5 (36")	3.78	5.88 (80") 7.63 (84")	6.77	10.63 (80") 12.88 (84")	INP	Smooth	
	42"	80" 84"	6	1-3/8" 1-3/4"	12.61	6.5	3.78	5.88 (80") 7.63 (84")	7.77	10.63 (80") 12.88 (84")	INP	Smooth	

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

⚠ WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.